



Gasoline Engine G.06 VTOL Fixed-Wing Heavy-Lift Gasoline UAV 4930mm Wingspan 49.5kg Payload 4864m Ceiling

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: GS
- Certification: CE, ISO, MIL-STD
- Model Number: G.06
- Minimum Order Quantity: 2
- Price: Negotiable
- Packaging Details: Military-standard transport case with pressure equalization valve
- Delivery Time: 35 working days
- Payment Terms: T/T, Western Union
- Supply Ability: 100



Product Specification

- Model: G.06
- Wingspan: 4930 Mm
- Length: 3217 Mm
- Airframe Material: Aviation Carbon Fiber Composite
- Engine: Gasoline Engine
- Payload: 49.5 Kg
- Take-off Mass: 179.4 Kg
- Cruise Speed: 53 M/s
- Endurance: 642 Min
- Max Range: 999 Km
- Altitude: 4864 M
- Protection Degree: IPX4
- Temperature: -20°C ~ 50°C
- Wind Resistance: Take-off Level 6 / Cruising Level 5
- Launch Method: Runway Take-off

for more products please visit us on uav-vtoldrone.com

G.06 Heavy-Lift Gasoline UAV

The **G.06** is a high-performance gasoline engine-powered VTOL fixed-wing unmanned aerial vehicle, engineered for **Cargo Delivery**. Featuring a 4930mm wingspan and 49.5kg payload capacity, this UAV delivers exceptional 642-minute endurance and 999km operational range. The entire airframe is constructed from **aviation-grade carbon fiber composite**, ensuring an optimal balance of structural strength and lightweight portability.

Equipped with an advanced flight control system and modular payload architecture, the G.06 supports rapid mission reconfiguration. Its VTOL capability eliminates the need for runways, enabling deployment from confined spaces. The IPX4 protection rating ensures reliable operation in challenging environmental conditions.





Key Features

Advanced VTOL Capability – Vertical takeoff and landing without runway infrastructure, deployable from ships, rooftops, or compact terrain

Full Carbon Fiber Airframe – Aerospace-grade composite construction for 125.6kg lightweight design with industry-leading strength-to-weight ratio

Gasoline Engine Power System – Optimized for 642min continuous flight with efficient fuel/energy management and redundant safety protocols

49.5kg Payload Capacity – Modular bay accommodates EO/IR cameras, LiDAR, SAR radar, communication relays, and custom mission equipment

999km Operational Range – Beyond-line-of-sight capability with secure datalink and autonomous return-to-home fail-safe

IPX4 Environmental Protection – Reliable operation in rain, dust, and extreme temperatures from -20°C to 50°C

Specifications

Model	G.06
Wingspan	4930 mm
Length	3217 mm
Airframe Material	Aviation Carbon Fiber Composite
Engine	Gasoline Engine
Payload	49.5 kg
Maximum Takeoff Weight	179.4 kg
Cruise Speed	53 m/s
Endurance	642 min

Max Range	999 km
Service Ceiling	4864 m
Protection Degree	IPX4
Launch Method	Runway Take-off

FAQ

▼ What missions is the G.06 best suited for?

The G.06 is optimized for **Cargo Delivery** operations, with its 49.5kg payload and 999km range making it ideal for extended-duration missions requiring reliable beyond-line-of-sight communication.

▼ Can the payload configuration be customized?

Yes, the modular payload bay supports rapid swapping between EO/IR gimbals, LiDAR scanners, multispectral cameras, SAR systems, and communication relay equipment based on mission requirements.

▼ How does the VTOL transition work?

The G.06 uses a seamless transition flight controller that automatically manages the conversion from vertical hover to fixed-wing cruise flight, requiring no manual pilot intervention during transition.

▼ What training is required to operate this UAV?

Basic operator training typically takes 3-5 days, covering mission planning, pre-flight checks, emergency procedures, and data post-processing. Advanced payload operation training is available separately.



Guangzhou Gesai Intelligent Electronic Technology Co., Ltd.



Kellyyangjing2021@outlook.com



uav-vtoldrone.com

Fuli Yingtong Building, the Pearl River New Town, Tianhe District, Guangzhou, Guangdong, China